





### TWEED

DESCRIPTION Mini Surface Mounted Downlight

CODES

FINISHES White, Black, Copper, Brass, Stainless Steel,

Custom, Aged Copper, Aged Brass

COLOUR TEMP 2700K, 3000K

BEAM ANGLE 38 CRI ≥90 LUMEN OUTPUT 420Lm WATTAGE

FIXTURE VOLTAGE 24V DC Constant Voltage

DIMMING Based On Driver and Voltage Selection

DRIVER Remote Driver Required DRIVER OPTIONS Non-Dim, Phase, Touch, DALI

IP RATING IP66

Notes: All data stipulated are nominal values based on 2700K with accuracy of  $\pm$  5%.






















# TWEED

## MANUFACTURING OPTIONS

FIXTURE					DRIVER
CODE	FINISH	ССТ	BEAM ANGLE	VOLTAGE	DIMMING
3452	WH - White	<b>27</b> - 2700K	<b>38</b> - 38° Medium	24V - 24V DC	ND - Non-Dim
	BLK - Black	<b>30</b> - 3000K			PH - Phase Dim
	CU - Copper				TH - Touch Dim
	BR - Brass				DA - DALI
	SS - Stainless Steel				
	AC - Aged Copper				
	AB - Aged Brass				
	CF - Custom Finish				

Example Code: **3455\_CU\_27\_38\_24V** 

Notes:

\* 240V AC Fixture are only available with Integral Back Plates. A non-dimmable AC to DC driver is provided inside the Back Plate.

Phase dimable drivers are not recommended for 24V DC fixtures due to possible flickering, but can be provided upon request.